

Description	Unit	Minimum	Maximum	Note
I-Materials composition				
1 NYL//LLDPE	Micron	15//30	15//150	
2 OPP//CPP	"	20//20	40//50	
3 OPP//MCP	"	20//20	30//40	
4 OPP//LLDPE	"	20//30	40//40	
5 OPP//MPET//CPP	"	20//12//25	20//12//40	
6 OPP//MPET//LLDPE	"	20//12//30	20//12//150	
7 OPP//ALU//LLDPE	"	20//7//30	20//7//100	
8 PET//CPP	"	12//20	12//50	
9 PET//MCP	"	12//20	12//40	
10 PET//LLDPE	"	12//30	12//150	
11 PET//MPET//LLDPE	"	12//12//50	12//12//100	
12 PET//ALU//LLDPE	"	12//7//40	12//7//150	
II-Printing Characteristics				
Printing type	Reverse			ROTOGRAVURE PRINT.
Colour printed	-	0	10	INCLUDED MATT VANIHSI
III-Product's Dimension				
Width	mm.	60	400	
Hight	mm.	100	700	
Top/Center seal area	mm.	5	40	
V-Cut / O-Cut	-	1	2	ON REQUEST.
IV-Bond Strength	kgf/15mm		Depend on materials composition.	
V-Seal Strength	kgf/15mm		Depend on materials composition.	
VI-O₂TR	cc/m ² /24		Depend on materials composition.	
VII-WVTR	gm/m ² /24		Depend on materials composition.	
VIII-Product Shelf life	Months	-	18	
IX-Packing	pcs/pack	50	100	Depend on size.
X-Minimum order quantity (MOQ)	Pcs	50,000	-	Depend on size.
XI-Lead time	Day	30	45	

XII-Important Notice;

All above data is a range of standard was measured, product characteristics can be change by thickness or materials compositions. Please request on your needs.