

Description	Unit	Minimum	Maximum	Note
<b>I-Materials composition</b>				
1 NYL//LLDPE	Micron	15//30	15//150	
2 OPP//CPP	"	20//20	40//50	
3 OPP//MCP	"	20//20	30//40	
4 OPP//LLDPE	"	20//30	40//40	
5 OPP//MPET//CPP	"	20//12//25	20//12//40	
6 OPP//MPET//LLDPE	"	20//12//30	20//12//100	
7 OPP//ALU//LLDPE	"	20//7//30	20//7//100	
8 PET//CPP	"	12//20	12//50	
9 PET//MCP	"	12//20	12//40	
10 PET//LLDPE	"	12//30	12//150	
11 PET//MPET//LLDPE	"	12//12//50	12//12//100	
12 PET//ALU//LLDPE	"	12//7//40	12//7//140	
<b>II-Printing Characteristics</b>				
Printing type	Reverse			ROTOGRAVURE PRINT.
Colour printed	—	0	10	INCLUDED MATT VANIHSI
<b>III-Product's Dimension</b>				
Width	mm.	80	300	
Hight	mm.	120	370	
Bottom gusset (BG)	mm.	15	50	
Side/Bottom seal area	mm.	5	20	
Corner cut	—	4	4	On Request.
Zipper/O-Cut/V-Cut/Peghole	—			On Request.
<b>IV-Bond Strength</b>				
	kgf/15mm			Depend on materials composition.
<b>V-Seal Strength</b>				
	kgf/15mm			Depend on materials composition.
<b>VI-O<sub>2</sub>TR</b>				
	cc/m <sup>2</sup> /24			Depend on materials composition.
<b>VII-WVTR</b>				
	gm/m <sup>2</sup> /24			Depend on materials composition.
<b>VIII-Product Shelf life</b>				
	Months	—	18	
<b>IX-Packing</b>				
	pcs/pack	50	100	DEPEND ON SIZE.
<b>X-Minimum order quantity (MOQ)</b>				
	Pcs	50,000	—	DEPEND ON SIZE.
<b>XI-Lead time</b>				
	Day	45	60	

**XII-Important Notice;**

All above data is a range of standard was measured, product characteristics can be change by thickness or materials compositions. Please request on your needs.