

Description	Unit	Minimum	Maximum	Note
<b>I-Materials composition</b>				
1 PET SHRINK	Micron	30	40	
2 PET SHRINK/Hotmelt	Micron	30/2	40/3	
<b>II-Printing Characteristics</b>				
Printing type	Reverse			ROTOGRAVURE PRINT.
Colour printed	–	0	8	
<b>III-Product's Dimension</b>				
<b>a.) Roll type</b>				
Reel Width	mm.	40	300	
Length/Roll	mm.	500	1,000	
Paper Core	inc.	3	6	
<b>b.) Tube type</b>				
Width	mm.	40	300	
Length	mm.	40	500	
<b>IV-Bond Strength</b>	kgf/15mm			N/A
<b>V-Seal Strength</b>	kgf/15mm			N/A
<b>VI-O<sub>2</sub>TR</b>	cc/m <sup>2</sup> /24			N/A
<b>VII-WVTR</b>	gm/m <sup>2</sup> /24			N/A
<b>VIII-Product Shelf life</b>	Months			N/A
<b>IX-Packing</b>	pcs/pack			DEPEND ON SIZE.
<b>X-Minimum order quantity (MOQ)</b>	Pcs	100,000	–	DEPEND ON SIZE.
<b>XI-Lead time</b>	Day	21	30	
<b>XII-Storage Conditions</b>				
Shelf life	Month	–	6	
Guarantee period	Month	–	6	
Storage Temperature	°C	5	25	
Storage Humidity	%RH	70	90	
Note; Guarantee period from manufacturing date is made, Complaints or rejection are accepted within 6 Mont Product shelflife can be exceed 6 months depending on storage conditions.				

**XIII-Important Notice;**

All above data is a range of standard was measured, product characteristics can be change by thickness or materials compositions. Please request on your needs.