

Description	Unit	Minimum	Maximum	Note
<b>I-Materials composition</b> 1 PVC SHRINK	Micron	30	40	
<b>II-Printing Characteristics</b> Printing type Colour printed	Reverse –	0	8	ROTOGRAVURE PRINT.
<b>III-Product's Dimension</b> <b>a.) Roll type</b> Reel Width Length/Roll Paper Core <b>b.) Tube type</b> Width Length	mm. mm. inc. mm. mm.	40 500 3 40 40	300 1,000 6 300 500	
<b>IV-Bond Strength</b>	kgf/15mm			N/A
<b>V-Seal Strength</b>	kgf/15mm			N/A
<b>VI-O<sub>2</sub>TR</b>	cc/m <sup>2</sup> /24			N/A
<b>VII-WVTR</b>	gm/m <sup>2</sup> /24			N/A
<b>VIII-Product Shelf life</b>	Months			N/A
<b>IX-Packing</b>	pcs/pack			DEPEND ON SIZE.
<b>X-Minimum order quantity (MOQ)</b>	Pcs	100,000	–	DEPEND ON SIZE.
<b>XI-Lead time</b>	Day	21	30	
<b>XII-Storage Conditions</b> Shelf life Guarantee period Storage Temperature Storage Humidity	Month Month °C %RH	– – 5 70	6 6 25 90	

Note; Guarantee period from manufacturing date is made, Complaints or rejection are accepted within 6 Month  
Product shelflife can be exceed 6 months depending on storage conditions.

**XIII-Important Notice;**

All above data is a range of standard was measured, product characteristics can be change by thickness or materials compositions. Please request on your needs.