

Description	Unit	Minimum	Maximum	Note
I-Materials composition				
1 NYL//LLDPE	Micron	15//100	15//150	
2 PET//LLDPE	"	10//100	12//150	
3 PET//NYL//LLDPE	"	10//15//90	12//25//150	
4 PET//ALU//LLDPE	"	10//6.5//90	12//9//150	
5 PET//ALU//NYL//LLDPE	"	10/6.5//15//90	12//9//25//150	
II-Printing Characteristics				
Printing type	Reverse			ROTOGRAVURE PRINT.
Colour printed	—	0	10	INCLUDED MATT VANIHSI
III-Product's Dimension				
Width	mm.	45	300	
Hight	mm.	70	450	
Top seal area	mm.	5	20	
Side seal area	mm.	5	20	
Bottom seal area	mm.	5	20	
Side gusset	mm.	15	55	
Bottom gusset	mm.	15	55	
Corner cut	—	4	4	RECOMMENDED.
Shape die-cut	—			AVAILABLE ON REQUEST.
Spout type/Colour/Diameter	—			AVAILABLE ON REQUEST.
IV-Bond Strength	kgf/15mm		Depend on materials composition.	
V-Seal Strength	kgf/15mm		Depend on materials composition.	
VI-O₂TR	cc/m ² /24		Depend on materials composition.	
VII-WVTR	gm/m ² /24		Depend on materials composition.	
VIII-Product Shelf life	Months	—	18	
IX-Packing	pcs/pack	10	50	DEPEND ON SIZE.
X-Minimum order quantity (MOQ)	Pcs	50,000	—	DEPEND ON SIZE.
XI-Lead time	Day	45	60	

XII-Important Notice;

All above data is a range of standard was measured, product characteristics can be change by thickness or materials compositions. Please request on your needs.